



ABL ELECTRONIC SUPPLIES, INC.  
 1032-A CENTRAL DRIVE NW  
 CONCORD, NC 28027

PHONE/FAX: 704-784-4225/0255  
[SALES@ABLEWIRE-CABLE.COM](mailto:SALES@ABLEWIRE-CABLE.COM)  
[SALES@GROUNDSTRAPS.COM](mailto:SALES@GROUNDSTRAPS.COM)

**EXTRA FLEXIBLE GROUNDING AND BONDING STRAPS GS15 & GS115**



**FLEXIBLE FLAT TINNED COPPER BRAID GROUND STRAPS  
 GS15 UNINSULATED, FOR INSULATED CHANGE P/N TO GS115**

CREATE YOUR OWN PART NUMBER:

Add length in Inches (hole to hole) after part number, EXAMPLE: GS115-010-12BK-1/4-1/4 or GS15-010-12-1/4-1/4.

Insulation available in Black or Green/Yellow as well as other colors. Some ground straps available in 304 stainless steel with nickel-plated steel terminals. P/N: GS15SS or GS115SS Ask about availability.

**Please provide hole size for lugs when placing your order. Other braid spec. sizes available upon request subject to availability of stock.**

The amperage ratings shown are for non-insulated braid and provided as a guide only. These ratings will vary with service conditions, ambient temperature and proximity to other components. All dimensions are nominal.

AWG SIZE	CIRCULAR MIL AREA	NO & AWG OF STRAND	APPROX AMPS	NOM WIDTH	ABLE PART NO.
4/0	211200	2112 X 30	390	2.125	GS15-4/0
3/0	153600	1536 X 30	290	2.000	GS15-3/0
2/0	124800	1248 X 30	250	1.750	GS15-2/0
1/0	105600	1056 X 30	235	1.375	GS15-1/0
1	76800	768 X 30	195	1.000	GS15-001
2	67200	672 X 30	165	1.375	GS15-002
3	52800	528 X 30	145	1.500	GS15-003
4	38400	384 X 30	120	1.000	GS15-004
6	24000	240 X 30	93	0.500	GS15-006
7	21600	864 X 36	85	0.750	GS15-007
9	13200	528 X 36	62	0.625	GS15-009
10	9600	384 X 30	53	0.500	GS15-010
12	7200	288 X 36	40	0.375	GS15-012
14	4200	168 X 36	32	0.250	GS15-014