



ABL ELECTRONIC SUPPLIES, INC.

1032-A CENTRAL DRIVE NW

CONCORD, NC 28027

PHONE/FAX: 704-784-4225/0255

SALES@ABLEWIRE-CABLE.COM

SALES@GROUNDSTRAPS.COM

**FLEXIBLE FLAT TINNED COPPER BRAID GROUND STRAPS
SOLDER DIPPED ENDS WITH PUNCHED HOLES
GS16 UNINSULATED, FOR INSULATED CHANGE P/N TO GSI16**



CREATE YOUR OWN PART NUMBER: Add length in Inches (hole to hole) after part number.

EXAMPLE: GSI16-010-12BK-1/4-1/4 or GS16-010-12-1/4-1/4.

Insulation available in Black or Green/Yellow as well as other colors.

Please provide hole size to punch when placing your order. Other braid spec. sizes available upon request subject to availability of stock.

The amperage ratings shown are for non-insulated braid and provided as a guide only. These ratings will vary with service conditions, ambient temperature and proximity to other components. All dimensions are nominal.

AWG SIZE	CIRCULAR MIL AREA	NO & AWG OF STRAND	APPROX AMPS	NOM WIDTH	ABLE PART NO.
4/0	211200	2112 X 30	370	2.125	GS16-4/0
3/0	153600	1536 X 30	290	2.000	GS16-3/0
2/0	124800	1248 X 30	250	1.750	GS16-2/0
1/0	105600	1056 X 30	235	1.375	GS16-1/0
1	76800	768 X 30	195	1.000	GS16-001
2	67200	672 X 30	165	1.375	GS16-002
3	52800	528 X 30	145	1.375	GS16-003
4	38400	384 X 30	120	1.000	GS16-004
6	24000	240 X 30	93	0.500	GS16-006
7	21600	864 X 36	85	0.750	GS16-007
9	13200	528 X 36	62	0.625	GS16-009
10	9600	384 X 30	53	0.500	GS16-010
12	7200	288 X 36	40	0.375	GS16-012
14	4200	168 x 36	32	0.025	GS16-014